



# Lifting Full Digital Discussion Chairman Unit

## TS-0230

# Lifting Full Digital Discussion Delegate Unit

## TS-0230A



TS-0230



TS-0230A

### Feature

- \*Embedded lift design, with simple and elegant appearance .
- \*With coiled capacitor microphone, professional ultra-cardioid capacitor microphone core for high sensitivity and speech articulation, built-in speech circular red and green indicators.
- \*This Unit microphone adopts 48KHZ sampling rate, which is higher than the CD sound quality, more clear and bright. Built in DSP audio processor and no "poop-poop" low frequency sound.
- \*Support speech timing and timed speech function.
- \*Delegate unit is with apply for speech function, The chairman(with screen) can approve the application for speech.
- \*Internal feedback suppression function .
- \*With 5 Section EQ adjustment function, different sound effects can be adjusted according to the characteristics of the speaker's voice to achieve perfect effect.
- \*The chairman is with the priority function, can turn off all delegate units which are speaking.
- \*In the voice control mode, the chairman unit and the delegate unit can be activated by voice control and can adjust the voice sensitivity. When the delegate unit is turned on, if no speaking for 30 seconds , the microphone will automatically turn off, but the chairman is not limited by it.
- \*With RS232 and RS485 dual serial control connection.
- \*With 100M network transmission to realize hand in hand cascading, Sound quality will not be influenced by long distance transmission.
- \*Intelligent control of the microphone, mic can be opened when it completely goes up , and close automatically when it goes down.

Model	TS-0230/TS-0230A
Mic Type	Cardioid electret
Frequency Response	80Hz-16KHz
Mic Input Impedance	1KΩ
Sensibility	-46dBV/Pa
MAX SPL	125dB(THD>3%)
SNR	>80dB(A)
Dynamic Range	>80dB
THD	<0.1%
Power Consumption	3W
Standard	IEC60914
Control	RS232/RS485
Connector	6 cores aviation plug
Power Supply Of Mic	By the host,DC36V/3W
Power Supply for Controller	AC 110~240V 50/60HZ
Color	Silver
Sign-In Function	Physical button sign in
Wight	About 5.5 KG
Mic Pole Height(mm)	415
Size(L×W×H)(mm)	160×70×713
Installation	embedded
Hole Size of The Desk (Universal)(L×W)(mm)	145×66mm
Counterbore Size(mm)	162×72×4, circular: 4×R5