



Full Digital Conference System Chairman Unit With 4.3 Inch Capacitor Color Screen TS-0205/TS-0205A



TS-0205



TS-0205A

Feature

*This Unit microphone adopts 48KHZ sampling rate, which is higher than the CD sound quality, more clear and bright. Built in DSP audio processor and no "poop-poop" low frequency sound.

*Support speech timing and timed speech function.

*Delegate unit is with apply for speech function, e Tchairman can approve the application for speech.

*With feedbacksuppression function.

*The chairman and delegate unit is with voice control function and the voice sensitivity can be adjustable.

*With 5 Section EQ adjustment function, different sound effects can be adjusted according to the characteristics of the speaker's voice to achieve perfect effect.

*Chairman unit is with the priority function,can turn off all delegate units which are speaking.

*4.3 inch TFT true color touch screen,simple and friendly operation .

*With 100M network transmission to realize hand in hand

cascading, Sound quality will not be influenced by long distance transmission.

*With two sets of 3.5 mm stereo output sockets, to connect for recording or headset.

*With a 3.5mm audio input interface for headphone mic.

*Support voting, election, rating function, chairman unit can start voting, sign in function. Data statistics can be done in case of without PC.

*Conference unit is with automatic ID programming function and supports to select language receiving channel , the defaults is 15 + 1, user can set 31 + 1 and 63 + 1.

*Support tea service function, applicant can send message to background ,such as "tea service", "paper and pen service", or "manual service"

*Sign in, voting functions will be interface button mode, in stead of physical button mode.

*Support real-time display or background synchronization display for sign in, voting status.

Model	TS-0205/TS-0205A
Microphone Types	Cardioid electret
Frequency Response	80Hz~16KHz
Impedance	1KΩ
Sensitivity	-46 dBV/Pa
SPL MAX SPL	125dB(THD>3%)
SNR	>80dB(A)
Crosstalk	>70dB
Dynamic Range	>80dB
THD	<0.1%
Maxim Consumption	5W
Headphone Volume	>16
Headphone Volume	MAX 40mW
Headphone Jack	3.5mm Mono jack
Standards	IEC60914
Connector	With 1.8 m 6 cores aviation plug
Power Supply	DC36V Host power supply
Color	Gray
Voting Function	5 Buttons – Selection; 3 Buttons-Voting
Simultaneous Interpretation	1, 32, 64 Channels (default 16)
Sign-In	Touch button Sign-in
Screen	4.3 inch color screen
length of Mic Pole	415mm
Installation	Desktop
Wight	1kg
Dimension(L×W×H)	206×174.2×65.5mm