



Description

* Widely used in hotels, commercial buildings, supermarkets, schools, leisure and entertainment places, etc.

Feature

- * It is a speaker with PoE power supply, Dante-to-analog signal output, built-in DSP processing function, and full network digital amplifier module. It can be adjusted through PC software to meet different demands for sound quality. Audio transmission using Dante network protocol has the characteristics of avoiding interference from transmission lines, high fidelity, and no delay. The network transmission and simple engineering wiring can make the installation of amplifiers and speakers more convenient, safe and reliable.
- * PoE power supply: support IEEE802.3af/at/bt standards respectively.
- * DSP processing functions: including scene saving, scene import, scene export, reset, 5-band equalizer, high-pass filter, low-pass filter, treble enhancement, bass enhancement, limiter, gain, etc.
- * High-grade rear cover with flame retardant plastic.
- * High-end coaxial speaker unit composed of 4.5-inch mid-woofer and silk-film neodymium magnet tweeter.
- * The input interface adopts 10/100MRJ45, 1 audio channel Dante input. Support PoE power supply, PoE specification is compatible with 802.af/at/bt standard. It connects with CAT5 or higher network cable.

Model	T-205DT
Input Interface	10/100MRJ45, 1 audio channel Dante input. Support PoE power supply, PoE specification is compatible with 802.af/at/bt standard. It connects with CAT5 or higher network cable.
Output Power	Peak power: 60W; Rated power: 30W
Frequency Response	95Hz-20kHz
Thd+n	<0.3%
Snr	>90dB
Speaker Unit	4.5 inch woofer+1 inch silk film tweeter coaxial speaker
Hole Size	180mm
Product Size (mm)	213X145
Weight	1.8kg