



## Delegate Unit

Delegate control embedded software TS-0305A V1.0  
TS-0305A



### Feature:

- \* It adopts a 4.3-inch IPS full-color touch screen with a simple interface.
- \* The microphone adopts a short microphone rod and a high-sensitivity microphone core to support long-distance sound pickup.
- \* Uncompressed audio transmission technology. The sampling rate is up to 48K, and it can provide perfect sound quality with a bandwidth of 80Hz-16KHz.
- \* It adopts 100M network transmission. And the network connection adopts network cable hand in hand, which is convenient for wiring.
- \* Communication adopts standard TCP/IP protocol, and each unit can support ping packet function.
- \* Simultaneous interpretation supports 63+1 channels, and the unit has a dual-channel listening function, which can listen to different interpreter channels at the same time.
- \* With two 3.5mm headphone jacks, support listen to the sound of any one of 63+1 channels or connecting an external microphone.
- \* The chairman unit has the priority right to turn off the speaking of the delegate unit.
- \* Each unit has a built-in independent web server, which supports four language switching, adjustment of microphone ID number, microphone sensitivity, microphone EQ and other parameters.
- \* It has the function of speech timing and timed speech, and the delegate unit can apply for speaking.
- \* Internal feedback suppression function, voice control function, adjustable voice control sensitivity.
- \* With a 5-band EQ adjustment function. Different sound effects can be adjusted according to the voice characteristics of the speaker until the perfect effect is achieved.
- \* Support (disk) clock display function. It can display the time. Synchronize server time.
- \* Support the conference logistics service function. The microphone unit can send service of tea, paper pen, manual services and other requirements to the conference controller.
- \* Support voting function. There are multiple voting mode options, and the content of the options can be customized and sent to the unit for display.
- \* Support sign-in function. You can also disable and control the unit check-in, and other functions through the PC software.
- \* Support firmware upgrade function on the web page.
- \* Support the IP address sniffing function, the ID number, IP address and MAC address of unknown units can be found by PC software.

### Specification:

|                           |   |
|---------------------------|---|
| Model                     | TS-0305A  |
| Microphone type           | Electret condenser microphone                   |
| Microphone directivity    | Cardioid  |
| Frequency response        | 80Hz~16KHz                                      |
| Sensitivity               | --40±1dB (0dB=1V/Pa,at1KHz)                     |
| SNR                       | >80dB(A)  |
| Dynamic range             | >80dB   |
| Maximum power consumption | 3.0W  |
| Standard                  | IEC60914  |
| Power supply              | Conference controller power supply              |
| Color                     | Oxidized fine sand black                        |
| Dimension (LxWxH)         | 154.9×99×60.5mm (without microphone rod length) |
| Microphone rod length     | 240mm   |
| Installation method       | Desktop   |
| Weight                    | 1.01kg  |