



## High-End Stage Speaker

### TS-610T/TS-612T/TS-615T



\*Work with professional amplifier, pre-effects processor together, and it is suitable for the use of the return sound box in theater, large conference hall and multi-function hall.

\*Using 1pcs mid-bass unit and 1pcs annular polyethylene vibrating diaphragm compression tweeter unit.

\*Speaker Box using 15mm plywood production, light weight, wear-resistant spray paint treatment, external rigid hexagonal iron mesh, with dust-proof cotton posted inside.

\*The precise frequency divider optimizes the medium frequency expression of the human voice part.

\*The multi-lateral structure of the speaker box can be adjusted according to the requirements of the site.

Model	TS-610T	TS-612T	TS-615T
Impedance	8Ω	8Ω	8Ω
Frequency Response	60Hz-20KHz	50Hz-20KHz	45Hz-20KHz
Rated Power	300W	400W	500W
Peak Power	1200W	1600W	2000W
Sensitivity	98dB/W/M	99dB/W/M	100dB/W/M
Max SPL(Rated/Peak)	123dB/129dB	125dB/131dB	127dB/133dB
Coverage Angle	(H)80°(V)60°	(H)80°(V)60°	(H)90°(V)70°
Tweeter	1.4"compression tweeter unit×1	1.7"compression tweeter unit×1	1.7"compression tweeter unit×1
Bass	10"bass×1	12"bass×1	15"bass×1
Dimensions(H×W×D)	340×510×380 mm	380×585×440 mm	Height 395×width690×depth465 mm
Weight	17.5Kg	20.5Kg	26.5Kg