




# Professional Active Speaker (Built-in DANTE)

## TS-615DT



### Description:

It works with the DANTE audio processor to form a set of high-end entertainment and conference professional sound system with outstanding vocal performance. It is suitable for various high-end conference rooms and multi-function halls as the main speaker or auxiliary speaker.

### Feature:

- \* Adopt a 15" woofer and a 1.73" compressed tweeter.
- \* 15mm plywood housing, light weight, wear-resistant spray paint treatment and dust-proof net cotton inside.
- \* The frequency divider in precise design optimizes the vocal MF performance.
- \* Built-in DANTE function of dual network ports can realize hand-in-hand connection.
- \* Support high-quality and long-distance signal transmission.
- \* The entire series is equipped with efficient high-power amplifier modules and powerful audio processors. Through different applications of the DANTE audio processor supporting system, it supports comprehensive parameter settings, including parameter equalization, frequency division, delay, and limit.
- \* Multiple screw hoisting holes, a pole socket with a diameter of 35mm, various installation methods.

### Specification:

Model	TS-615DT
Impedance	8Ω
Frequency response	45Hz-20KHz
Rated power	450W
Peak power	1800W
Sensitivity	100dB/W/M
Maximum SPL(rated/peak)	127dB/133dB
Coverage angle	(H)80° (V)60°
Tweeter	1.73" compressed tweeter ×1
Woofer	15" woofer ×1
Line input sensitivity	0dB
Network port	DANTE protocol
Bandwidth	1000M
Dimension	660×435×430mm (H×W×D)
Weight	29.5Kg
Power supply	AC 220V 50Hz
Power consumption	360W