



*Work with TA professional amplifier, pre-effects processor together, formed a set of perfect sound and vocal performance outstanding high-end conference sound reinforcement system, and it is suitable for large banquet hall, multi-function hall, large conference rooms and auditorium,etc.,with the subwoofer can be used to do high-performance satellite boxes.

- *Using 1pcs mid-bass speaker unit and 1pcs compression tweeter unit.
- *The box is made of 15mm birch production, light weight and high grade transparent paint on the surface, with dust-proof screen posted outside.
- *The precise frequency divider optimizes power response and the medium frequency expression of the vocal part.
- *Multiple screw lifting holes, one 35 mm cylinder socket, multiple installation methods.

Model	TS-710H	TS-712H	TS-715H
Impedance	8Ω	8Ω	8Ω
Frequency Response	45Hz-20KHz	45Hz-20KHz	40Hz-20KHz
Rated Power	300W	45Hz-20KHz	500W
Peak Power	1200W	400W	2000W
Sensitivity	98dB/W/M	1600W	100dB/W/M
Max Spl(Rated/Peak)	123dB/129dB	99dB/W/M	127dB/133dB
Cover Range	(H)90°(V)80°	(H)90°(V)80°	(H)90°(V)80°
Tweeter	1.7"compression tweeter	1.7"compression tweeter	1.7"compression tweeter
	unit×1	unit×1	unit×1
Bass	10"bass×1	12"bass×1	15"bass×1
Dimension(H×W×D)	530×350×360 mm	615×380× 410 mm	670×440×470 mm
Weight	18.5Kg	23.6Kg	26.5Kg