

PROFESSIONAL MEETING MICROPHONE INSTRUCTION MANUAL

This product is specially designed and made for various kinds of meeting, lectures, broadcasting, recording occasion, etc. It adopts high quality condenser cartridge to make sure that the microphone has high sensitivity and good frequency response. Please read the following instruction carefully before use the microphone

Specifications:

1. Capsule Type: Condenser
2. Frequency Response: 40Hz-18KHz
3. Output Impedance: 75Ω Balanced
4. Sensitivity: -45dB
5. Polar Pattern: Hyper cardioid
6. Power Supply: Phantom 48V
7. Cable Length: 10meters
8. Max. Input Level: 128dB

Operation Instruction

1. Connect the microphone audio cable to mixer or other equipments (the equipments should supply phantom 48V)
2. Adjust the volume of the amplifier to the minimum level.
3. Turn on the power switch of the amplifier and meeting microphone, and then adjust the volume of the amplifier slowly to desired level.

Operating Suggestions

1. If the microphone is placed too close to speaker, it could generate feedback (Larsen effect). Avoid placing the microphone too close to the speaker, and avoid orienting its capsule toward the speaker. If, despite these practices, you hear feedback, please lower speaker volume.
2. Due to the microphone's very high sensitivity, be careful the microphone isn't dropped and avoid shock, as it could be damaged.
3. In order to maintain sensitivity and performance, avoid exposing the microphone to moisture or high temperatures.