



4.3 Inch Screen Voting Chairman Unit(Built in Sign IIC Card +

Electronic Nameplate) **TS-0203**

4.3 Inch Screen Voting Delegate Unit(Built in Sign IIC Card +

Electronic Nameplate) **TS-0203A**



Feature

*This Unit microphone adopts 48KHZ sampling rate, which is higher than the CD sound quality, more clear and bright. Built in DSP audio processor and no "poop-poop" low frequency sound.

*Support speech timing and timed speech function.

*Delegate unit is with apply for speech function, The chairman can approve the application for speech.

*With feedback suppression function.

*The Microphone has voice control function, can turn on the microphone intelligently by voice. The chairman and delegate unit is with voice control function and the voice sensitivity can be adjustable.

*With 5 Section EQ adjustment function, different sound effects can be adjusted according to the characteristics of the speaker's voice to achieve perfect effect.

*The chairman is with the priority function, can turn off all delegate units which are speaking.

*With 4.3 inch TFT touch screen, simple and friendly operation.

*With 100M network transmission to realize hand in hand cascading,

Sound quality will not be influenced by long distance transmission.

*With functions of ICcard for sign in, showing participants' unique characteristics.

*Support voting, election, rating function, chairman unit can start voting, sign in function. Data statistics can be done in case of without PC.

*With electronic nameplate, built in full view large LCD Screen to shows the participant's name, the display information can be updated by PC.

*Conference unit is with automatic ID programming function and supports to select language receiving channel, the defaults is 15 + 1, user can set 31 +1 and 63+1.

*Support Chinese and English interface display, one key to switch interface.

*Sign in, voting functions will be interface button mode, in stead of physical button mode.

*Support tea service functions, a key into the tea service.

*Support background message notification, support fire alarm linkage alarm interface.

*Support real-time display or background synchronization display for sign in, voting status.

Model	TS-0203/TS-0203A
Microphone Types	Cardioid Electret
Directivity	80Hz~16KHz
Input Impedance	1KΩΩ
Sensitivity	-46 dBV/Pa
MAX SPL	100dB (THD>3%)
SNR	>80dB
Crosstalk	>70dB
Dynamic Range	>80dB
THD	<0.1%
Maxim Consumption	5W
Headphone Load	>16Ω
Headphone Volume	MAX 40mW
Headphone Jack	3.5mm Mono jack
Standards	IEC60914
Connector	With 1.8 m 6 cores aviation plug
Power Supply	Host power supply DC 36V
Color	Black
Voting Function	Button Five – Selection; Button three--Voting
Simultaneous Interpretation	16, 32, 64 Channels (default 16)
Sign-In	Press key to Sign-in; IC card sign-in
IC Card	With contact IC card
Screen	4.3 inch color screen
Electronic Nameplate	5.5" Green Electronic nameplate
Wight	1.17kg
Mic Bar Length	415mm
Dimension (L×W×H)	218×135×63
Installation	Desktop Type