



# Full Digital Conference Embedded Chairman Unit

## TS-0223

# Full Digital Conference Embedded Delegate Unit

## TS-0223A



TS-0223



TS-0223A

## Feature

\*With full digital induction touch embedded design, delicate appearance, the touch panel with compact design, easy to operate, full of modern sense of science and technology.

\*Using the new CNC design, capacitive touch buttons, no mechanical noise, buttons with long life, waterproof design.

\*The microphone adopts 48KHZ sampling rate, higher than the CD sound quality, the voice is clear and bright. Built-in DSP audio processing, there is no low frequency sound.

\*Support speech timer and timing speech function.

\*Delegate unit apply for speech function, the chairman unit can approve the applicant.

\*Chairman unit has the priority function, which can turn off all delegate units during speaking.

\*With the feedback inhibition function, can effectively prevent the noise.

\*Microphone has voice-control model to open the microphone smartly.

\*5 Section EQ regulating function, different sound effects can be adjusted according to the characteristics of the speaker's voice, to achieve perfect effect.

\*Adopt 100m network transmission to realize hand-in-hand cascading, long-distance transmission will not influence the sound quality.

Model	TS-0223/ TS-0223A
Microphone Type	Heart shaped directivity electrets
Frequency Response	80Hz-16KHz
Microphone Input Impedance	1KΩ
Sensitivity	-46dBV/Pa
SPL Max SPL	125dB (THD>3%)
Noise-Signal Ratio	>80dB (A)
Dynamic Range	>80dB
THD	<0.1%
Power Dissipation	1.8W
Follow Specification	IEC60914
Connector	With 1.8 meters of aviation core 6
Power Supply Mode	Host power supply
Color	Grey
Sign In Function	Sign in by touch keys
Weight	0.5Kg
Microphone Stem Height	415mm
Installation Mode	Embedded
Table Hole Size	65×54mm
Dimension(L×W×D)	108×77×129mm