



Digital Chairman Unit (Discussion, Voting & IC Card)

TS-0627

Digital Delegate Unit (Discussion, Voting & IC Card)

TS-0627A



TS-0627



TS-0627A

Feature

- *Unique patented technology, specially designed anti-RF radio frequency interference tube, which can completely eliminate the noise, Showing a perfect high-level conference environment.
- *Unique patented design, Fully embodies the designer to grasp the vision of the world aesthetics.
- *Unique microphone head design, So that even if the speaker does not have the cotton cover, but also completely eliminate the "pupu" low-frequency impact.
- *Professional heart-shaped condenser microphone core, Very high sensitivity and voice clarity; And with a ring of red & green indicator light when speaking.
- *When the red ring light is on, it means somebody is speaking; when green is on, it means apply for awaiting speech.
- *It has function of suppress whistle, when microphone is open, the built-in speaker will be closed automatically.
- *With function of IC card to sign in.
- *Built-in speaker, headset jack, which can adjust the headset volume.
- *Use the professional 8 core aviation plug by cascading units, and with the metal fixed nut to avoid loosening and falling .
- *It has 1.8 meter 8 core connection line that is used full line of aluminum foil and waterline shield, which greatly reduce the

interference of strong electromagnetic waves on the wire, avoid "zizi" noise.

- *It is passive equipment, which is powered by the system controller, input voltage is 24V; belongs to the safe scope.
 - *Chairman unit has no limited by speakers qty.
 - *The Chairman unit has priority function to control conference sequence, can approve or reject the speaking application from delegate unit.
 - *Chairman unit has priority function of taking full control of the sequence of the meeting, can approve or reject the application for a delegate unit.
 - *5 There are 5 multi-functional buttons for voting, election and meeting evaluation. Using silicone keys, feel good.
 - *The button indicator has prompt function of real-time voting states. Speaking unit can apply or cancel to speak.
 - *It adopts full-view OLED screen with thin thickness and low power consumption.
 - *The display can show the operation of the vote, voting mode, sign-in mode.
 - *Chinese and English interface can be switched, with function of sending message, very convenient to notify participants.
- Note : with IC card,need to work with the ic card writer.

Model	TS-0627/TS-0627A
Microphone Type	cardioid directivity electret
Frequency Response	80Hz~16KHz
MIC Input Impedance	1KΩ
Sensitivity	-46 dBV/Pa
MAX SPL	125dB(THD>3%)
SNR	>80dB
Crosstalk	>70dB
Dynamic Range	>80dB
THD	<0.1%
MAX Power Consumption	3W
Headphone Load	8-32Ω
Headphone Volume	MAX 40mW
Headphone Interface	3.5mm mono jack
Standard	IEC60914
Connector	With 6-core air cable of 1.8M
Hand By Hand Expansion Port	unavailable
Power Supply Type	DC24V power supply from main controller
Color	silver gray
Voting Function	5 key voting, 3 key voting
Sign In Function	key to sign in, IC card to sign in
IC Card	with
Display Screen	OLED all sight low power consumption
Weight	0.8kg
Microphone Height	460mm
Dimension(mm)	161(L)×141(W)×40(H)
Mounting Method	Tabletop type