



Paperless Integrated Lifter (paperless ultra-thin 15.6-inch capacitive

LCD screen with microphone lifter, intelligent elevation adjustable 30 degrees)

TS-F156MT



Description

*The product adopts intelligent control technology, taking intelligent terminal as application concept, adopting original guide rail design. One key operation can automatically complete starting, LCD screen up, elevation and other actions, beautiful desktop, space-saving as the purpose, easy to use. With anti-theft, anti-dust, beautify desktop and other function. It can be widely used in conference, office hotel, teaching studio and other occasion, to meet the customer systems development diversity, and office automation environment demand. It is one ideal assistant of your office and teaching.

Feature

*With ultra-thin HD touch screen and lifter integrated design, no exposed cable, no connection backboard, no exposed screws, ensure a nice overall appearance of touch display screen.

*Built in an elevating microphone, microphone up and down with automatic straightening function, when MIC bending, it will be automatically straightening when machine close, won't be damaged.

*Equipment use all-aluminum structure, high-quality aluminum with CNC carved processing, display frame and chassis are made of aluminum alloy, to make equipment refined, lightweight, beautiful.

*Equipment surface treatment is anodized, bright color.

*Equipment panel thickness of only 3mm, width of only 70mm, small footprint.

*Adopt imported steel wire, cooperated with high precision guide rail and linear bearing, AC geared motor as driving force, reduce noise to minimum.

*15.6-inch ultra-thin LCD touch screen display, resolution up to 1920*1080P, clear and bright display, adjustable backlight design, to prevent fatigue caused by too bright or too dark.

*Support HDMI and VGA two channel signal input, when there is only one signal input, the screen will automatically recognize this signal, when these two signal input at the same time, can be manually switched from panel key, when no signal input, the screen will automatically enter into power saving mode.

*The device can be centrally controlled through central control software, can be controlled by the host computer, one key can make all device in the room go up or down.

*Built-in loop-through output power outlet, can power supply to the terminal to reduce terminal power outlet wiring, make project site wiring more neat and beautiful.

*With USB port on the desktop panel, the user can read the file in the USB or upload files to the USB.

Model	TS-F156MT
Touch Screen	Support
Lifting Time	28S
Elevation Angle	0-30°
Case Size	540*60*647mm
Panel Size	555*70*3mm
The Lifting Hole Size	388*21.5mm
Desk Cut-Out Size	542*62mm
Panel Chintay Size	556*71*3mm
Working Environment	-20℃~50℃, relative humidity≤70%
Screen Size	15.6"
Screen Aspect Ratio	16:9
Resolution	1920*1080
Video Port	1 VGA、1 HDMI
Control Port	2 groups of 232/485 input and output ports to control microphone and screen lifting, support hand-by-hand connection, 1 USB port for switch on and off, 1 USB port for data transmission
Microphone Interface	Aviation 6 pin interface, support hand-by-hand connection
Mic Rod Length	415mm
Backlight Type	WLED, 15K hour, with LED driver
Contrast	600:1
Brightness	300cd/m²
Viewing Angle	45/45/20/40(Typ.)
Screen Thickness	9.7mm
Power Supply	AC 220V 50-60/HZ
Power Consumption	25W
Weight	12Kg