Digital Conference Dedicated Suppressor

TS-234

Feature

*With new adaptive algorithm, there is no need to debug. Accurate, reliable and easy to use, system gain can be improved to 9-15 db.

*Built-in pressure-limit function can make the signal output keep in high fidelity even signal input in large dynamic situation.

*Direct/noise suppression switch makes the system controlled by one key when feedback suppressor is not used. This makes the sound system more simple and easy to operate.

*With wireless microphone interface and potentiometer to adjust the intensity of the input signal, it is more convenient to connect devices.

*Signal input and output have XLR and RCA port which makes the system connection more convenient.

*Support international general wide voltage range, reach AC100V ~ 240V.

Model	TS-234
Rated Input Level	2.2dBU
Max Line Input Level	15dBU
Line Input Port	RCA, XLR
Wireless Microphone Rated Input Level	-19.7dBU(Sensitivity is adjustable)
Rated Output Level	2.2dBU
Wireless Microphone Input Port	φ6.3MIC
Line Output Port	RCA, XLR
Line Input Impedance	Unbalanced: 10KΩ, balanced input20KΩ
Wireless Microphone Input Impedance	1KΩ
Line Output Impedance	50Ω
S/N Ratio	≥60dB
Frequency Response	50~14.50kHz±3dB
Ground Resistance	≤0.1Ω
Power Consumption	5W
Power Supply	~100V-240V 50/60HZ
Dimensions	484×209×45mm
Weight	2.76Kg