



### Description

It is a 10.1-inch touch screen developed based on the Android system. It uses a high-definition screen with a resolution of 1280\*800. The picture quality is exquisite. It has a built-in 200W camera and speaker. Support POE power supply, central control, and indicator light function for the feedback of different scene states. It is suitable for various medium and high grade meeting rooms, control centers and other occasions. It is a high-end man-machine interface device.

### Feature

- \* Thin screen, 27mm thickness, integrated high-precision middle frame mold.
- \* Built-in 200W camera and 2\*2W speaker.
- \* Support 1-channel RJ45 network interface, 100M network transmission.
- \* Support multi-touch capacitive screen.
- \* Full-view HD screen with a resolution of 1280\*800.
- \* Support POE power supply for simple wiring.
- \* Support DC12V power supply.

### Specification

Model	TS-9110A
CPU	RK3288, quad-core, 1.8G
RAM	2GB
Memory	8GB
Operating system	Android7.1
Display screen	HD IPS screen
Resolution	1280*800
View area	217(H)x135.6mm(V)
Contrast	1300
Brightness	280cd/m <sup>2</sup>
Screen ratio	16:9
Touch screen	10.1 inch capacitive touch screen
Light	Left and right LED light bar. Status light can change color
Media player	Video format: MPEG-1, MPEG-2, MPEG-4, H.263, H.264, VC1, RV Audio format: MP3/WMA/AAC Picture format: jpeg
Speaker	2*2W
Camera	Front 200W
Communication port	1 100M network port
Other port	USB*2
DC	DC power supply 12V input
POE	Support, IEEE802.3at/af
Power supply	Support POE/DC12V power supply
Operating temperature	0-40°C
Colour	Silver white
Weight	0.7kg
Dimension (L×W×D) mm	253mm×163mm×27mm